



Expedition Vehicle Auto-Levelling System

The Redfoot Maxi EQ Smart Level Telescopic system is custom-designed for all expedition vehicle chassis'. It is no wonder this system has become the number one levelling choice for expedition vehicle owners.



- ✓ Bluetooth capability to allow remote operation on your smart device
- ✓ One touch, push button Auto-level operation
- ✓ Audio and visual prompts notify user when levelling is in progress and complete

Benefits

- ✓ Easy bolt-on solution
- ✓ Large foot plate to prevent sinking
- ✓ Simple plug and play installation
- ✓ Huge lifting capacity
- ✓ Stow jacks quickly and easily with auto "All-Retract" feature
- ✓ User-friendly design, ensuring effortless operation
- ✓ Prevents vehicle rocking and motion
- ✓ Light weight
- ✓ Manual override feature comes standard
- ✓ Field adjustable null for optimal levelling

Technical Information



Specification	Redfoot Maxi EQ Smart Level Telescopic Medium		Redfoot Maxi EQ Smart Level Telescopic Large	
Part Number	EQMA-600-600 (12V)	EQ24V-600-600 (24V)	EQMA-1070-1070 (12V)	EQ24V-1070-1070 (24V)
Cylinder Size	1st Stage Bore: 70mm 2nd Stage Bore: 50mm		1st Stage Bore: 100mm 2nd Stage Bore: 75mm	
Stroke	600mm		1070mm	
Set Travel Clearance for Auto-Level Operation	MAX 450mm		MAX 450mm	
Pump Type	12Vdc (1600W)	24Vdc (2200W)	12Vdc (1600W)	24Vdc (2200W)
Relief Pressure	3000 PSI	3000 PSI	3000 PSI	3000 PSI
Harness	Yes		Yes	
Hose Kit	Custom		Custom	
Optional Brackets	Weld-on		Weld-on	
Manual Override	Yes		Yes	
Foot Plate Diameter	160mm		180mm	
System Weight (Dry) Add approx. 10kg for fluid + hoses	160kg		175kg	
Max Lift Capacity	10 tonnes		28 tonnes	
Battery Size Minimum	200 Amp Hr 12Vdc	100 Amp Hr @24Vdc	200 Amp Hr 12Vdc	100 Amp Hr 24Vdc
Bluetooth Capability	Yes		Yes	
Pump Dimensions	L 630mm x W 240mm x H 250mm		L 590mm x W 230mm x H 470mm	



REDFOOT
LEVELLING

Unit 1, 7 Abeles Street

Baringa QLD 4551

☎ (07) 5228 0211

✉ info@redfootlevelling.com

🌐 www.redfootlevelling.com

DEALER INFORMATION