



Light Rigid Vehicle Auto-Levelling System

The Redfoot EQ Smart Level system is custom-designed for all light-rigid vehicle chassis'. It is no wonder this system has become the number one levelling choice for light-rigid vehicle owners.



- ✓ Bluetooth capability to allow remote operation on your smart device
- ✓ One touch, push button Auto-level operation
- ✓ Audio and visual prompts notify user when levelling is in progress and complete

Benefits

- ✓ Easy bolt-on solution
- ✓ Large foot plate to prevent sinking
- ✓ Simple plug and play installation
- ✓ Huge lifting capacity
- ✓ Stow jacks quickly and easily with auto "All-Retract" feature
- ✓ User-friendly design, ensuring effortless operation
- ✓ Prevents vehicle rocking and motion
- ✓ Light weight
- ✓ Manual override feature comes standard
- ✓ Field adjustable null for optimal levelling

Technical Information



Specification	Redfoot Elite EQ Smart Levelling Small		Redfoot MAXI EQ Smart Levelling Large	
Part Number	EQEL-15-15 (12V)	EQ24V-15-15 (24V)	EQMA-18-18 (12V)	EQ24V-18-18 (24V)
Cylinder Size	4 x 15" (2" bore)		4 x 18" (3" bore)	
Stroke	360mm		450mm	
Set Travel Clearance	200-250mm		250-300mm	
Pump Type	12Vdc (800W)	24Vdc (2200W)	12Vdc (1000W)	24Vdc (2200W)
Relief Pressure	2800 PSI	3000 PSI	2800 PSI	3000 PSI
Harness	Yes		Yes	
Hose Kit	Custom		Custom	
Optional Brackets	Weld-on		Weld-on	
Manual Override	Yes		Yes	
Foot Plate Diameter	250mm		300mm	
System Weight (Dry) <small>Add approx. 10kg for fluid + hoses</small>	90kg		145kg	
Max Lift Capacity	16 tonnes		28 tonnes	
Battery Size Minimum	200 Amp Hour @12Vdc	100 Amp Hour @24Vdc	200 Amp Hour @12Vdc	100 Amp Hour @24Vdc
Bluetooth Capability	Yes		Yes	
Pump Dimensions	L 530mm x W 230mm x H 215mm	L 650mm x W 250mm H 250mm	L 580mm x W 250mm x H 210mm	L 650mm x W 250mm H 250mm



REDFOOT
LEVELLING

Unit 1, 7 Abeles Street

Baringa QLD 4551

☎ (07) 5228 0211

✉ info@redfootlevelling.com

🌐 www.redfootlevelling.com

DEALER INFORMATION